



# INSTALLATION INSTRUCTIONS

**This filter fits:** SEE CATALOG FOR CURRENT APPLICATIONS

**\*FREE K&N DECAL** To register your warranty, please see us online at [knfilters.com/register](http://knfilters.com/register). **FREE K&N DECAL \***

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modification will be required. However the following procedures **MUST** be followed to ensure the proper fit and seal of the K&N Filter.

## INSTALLATION:

- 1) Remove the airbox lid.
- 2) Remove the filter element from the airbox base.
- 3) Wipe out any dust or dirt from the airbox lid with a damp rag.
- 4) Using the supplied tube of grease, liberally apply a coat of grease to the sealing edge of the filter. The ribs that run around the perimeter of the filter creates a groove to capture the grease. Additional sealing grease may be purchased in an 6 oz. tube from any K&N retailer.
- 5) Install the pre-oiled K&N Filtercharger® into the airbox lid. Be certain that the filter is properly seated into lid.
- 6) While holding the filter into the lid, re-install lid onto the base and close.

**THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.**

Apply a coat of grease to the space between the ribs that run around the perimeter of the filter.

