



INSTALLATION INSTRUCTIONS

MAKE: Dodge
MODEL: RAM 2500/3500
YEAR: 2003-2007
ENGINE: L6-5.9L (td) Cummins

Exhaust Header
304 Stainless Steel
48-32018



Parts Included:

- (P/N: 05-145214) Header

Hardware Included:

- (P/N: 05-60383) Gasket Set (x1)
- (P/N: 05-60035) Bracket (x1)
- (P/N: 05-60034) Channel Bracket (x1)
- (P/N: 03-50214) Stud: M10 x 1.5 x 50mm (x3)
- (P/N: 03-50343) Steel Spacer (x9)
- (P/N: 03-50346) Screw Hex (x9)
- (P/N: 03-50383) Nut, M10 (x7)
- (P/N: 03-50410) Plug, 1/8" NPT (x2)

CAUTION: Allow time for your vehicle to cool down prior to installation. When working on or under your vehicle proceed with caution. Exhaust systems reach high temperatures and may cause serious burns. Wear protective safety equipment; eye goggles and gloves to ensure a safe installation. aFe recommends professional installation on our products.

Step 1: Disconnect both of the battery cables.

Step 2: Remove air filter housing and air intake tube from vehicle.

Step 3: Remove the heat shield from the stock exhaust manifold (this will not be reused)

Step 4: Disconnect the exhaust down-pipe, turbo outlet, oil supply line, oil return line, electrical connection (if applicable).

Step 5: Disconnect the water line bracket nearest the firewall, under the exhaust manifold, using a 15mm socket. Cut the bracket 2" from the water line.

***NOTE:** The stock manifold and turbo will come out together.

Step 6: Remove the stock exhaust manifold and the turbo by removing the twelve manifold bolts using a 13mm socket.

Step 7: Prepare the mating surfaces on the head and turbo for a better seal.

Step 8: Install the three supplied M10x1.50x50mm studs on the bottom row of cylinders 3, 4, and 5.

Step 9: Install the turbo and the factory gasket on the aFe turbo header.

(Continue Page 2)



INSTALLATION INSTRUCTIONS

MAKE: Dodge
MODEL: RAM 2500/3500
YEAR: 2003-2007
ENGINE: L6-5.9L (td) Cummins

Exhaust Header
304 Stainless Steel
48-32018



Parts Included:

- (P/N: 05-145214) Header


Hardware Included:

- (P/N: 05-60383) Gasket Set (x1)
- (P/N: 05-60035) Bracket (x1)
- (P/N: 05-60034) Channel Bracket (x1)
- (P/N: 03-50214) Stud: M10 x 1.5 x 50mm (x3)
- (P/N: 03-50343) Steel Spacer (x9)
- (P/N: 03-50346) Screw Hex (x9)
- (P/N: 03-50383) Nut, M10 (x7)
- (P/N: 03-50410) Plug, 1/8" NPT (x2)

CAUTION: Allow time for your vehicle to cool down prior to installation. When working on or under your vehicle proceed with caution. Exhaust systems reach high temperatures and may cause serious burns. Wear protective safety equipment; eye goggles and gloves to ensure a safe installation. aFe recommends professional installation on our products.

Step 10: Install the aFe turbo header using the nine bolts and spacers, and the three nuts provided in the kit

*aFe recommends replacement of old gaskets (not supplied). Apply anti-seize to the bolts before installing. Tighten the bolts using the recommended factory torque procedure as shown. Tighten to 32ft./lbs.



Step 11: Install the supplied waterline bracket to the factory water line using the supplied M8x1.25x25 bolt and the factory hardware.

Step 12: Install the supplied 1/8" NPT plugs into the exhaust manifold.

Step 13: Reinstall the exhaust down-pipe, turbo outlet, oil supply line, oil return line, and the electrical connection (if applicable) using the factory hardware.

Step 14: Reinstall the air intake tube and air filter housing.

Step 18: Reconnect the batteries. Your installation is now complete. Thank you for choosing aFe power.

***Note:** Retighten all connections after approximately 100-200 miles.